



UvA-DARE (Digital Academic Repository)

Bridging Representations of Laws, of Implementations and of Behaviours

Sileno, G.; Boer, A.; van Engers, T.

DOI

[10.3233/978-1-61499-609-5-169](https://doi.org/10.3233/978-1-61499-609-5-169)

Publication date

2015

Document Version

Author accepted manuscript

Published in

Legal knowledge and information systems

[Link to publication](#)

Citation for published version (APA):

Sileno, G., Boer, A., & van Engers, T. (2015). Bridging Representations of Laws, of Implementations and of Behaviours. In A. Rotolo (Ed.), *Legal knowledge and information systems: JURIX 2015: the Twenty-Eight Annual Conference* (pp. 169-172). (Frontiers in Artificial Intelligence and Applications; Vol. 279). IOS Press. <https://doi.org/10.3233/978-1-61499-609-5-169>

General rights

It is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), other than for strictly personal, individual use, unless the work is under an open content license (like Creative Commons).

Disclaimer/Complaints regulations

If you believe that digital publication of certain material infringes any of your rights or (privacy) interests, please let the Library know, stating your reasons. In case of a legitimate complaint, the Library will make the material inaccessible and/or remove it from the website. Please Ask the Library: <https://uba.uva.nl/en/contact>, or a letter to: Library of the University of Amsterdam, Secretariat, Singel 425, 1012 WP Amsterdam, The Netherlands. You will be contacted as soon as possible.

Bridging Representations of Laws, of Implementations and of Behaviours

Giovanni SILENO^{a,1}, Alexander BOER^a and Tom VAN ENGERS^a

^a*University of Amsterdam, Leibniz Center for Law, The Netherlands*

Abstract. To align representations of law, of implementations of law and of concrete behaviours, we designed a common ground representational model for the three domains, based on the notion of position, building upon Petri nets. This paper reports on work to define subsumption between positional models.

Keywords. Representational alignment, Positional programming, Logic Programming, Petri Nets, Subsumption

Introduction

While law is often expressed in general terms, addressing classes of persons and abstract normative notions, courts and public administrations are required to translate those provisions in actual, contextualized behavioural terms. To facilitate this *contextualization* process, one of the objectives of our current research (cf. [3,2]) is to support alignment between representations of legal-institutional mechanisms, representations of implementations in business processes in administrative organizations, and representations of social behaviour as in case law. Pursuant to our work in e.g. [3,2], our present objective is to work on an operational definition of subsumption – covering instantiation, generalization, and, to some degree, nonmonotonic abstraction – for positional models belonging to different views, to aid the organization of these models in a component library.

The core problem – of ontological, epistemic and normative *frictions* (cf. Schlag [8] on arguments in courts) – is not specific to law; The semi-formal process of law eases, and is plausibly *meant* to reduce, such frictions. This contextualization process exists in any agency (individual or organization). From an *internal perspective* to agency, social norms provide reasons for the agent to promote or demote certain action-selections, or even create the possibility of certain action-selections (via institutional power). In contrast, behavioural representations that take an *external perspective* to agency have a focus on *observable* interactions between agent identities, without relying on internal mechanisms. Internal and external perspectives are separated by degree of *granularity*, and by making reference or not to the *mechanisms* which are supposed to produce the events. Similar dichotomies can be found in internal and external views in modeling, cf. UML; or in software engineering, with the notions of *orchestration* and *choreography*. The two perspectives can be seen opposite poles in a representational spectrum to describe, explain and prescribe behaviour.

¹Corresponding author: g.sileno@uva.nl.

	they have behaved	they usually behave	they should behave
how	occurrence description	pattern description	normative definition
why	occurrence explanation	behavioural mechanism	norm-creating mechanism

Table 1. What agents may tell with narratives: a simple taxonomy. *They* targets both self and/or others.

1. Narratives and Positional modeling

Narratives – cases in law – are the most expressive medium humans use to share knowledge about *how* and *why* they have behaved in a certain way, or *usually* behave, or *should* behave or have behaved. Table 1 shows a simple taxonomy that summarizes the possible contents that may be acquired from narrative, revealing the presence of *ontological stratification* [1, p. 38], with at least six *strata* whose positions we need to align. A *position* in our terms is a *local state* of the system that can be (locally) related to other positions in dimensional terms. For instance, in a classic logic system, each proposition can be put in relation at least with its negation by definition, but analytic philosophy (internal vs external negation) and logic programming (classic vs default negation/negation as failure) recognize a practical multi-dimensional problem. We recently presented two contributions about the use of positions in institutional and intentional modeling. First, we remapped Hohfeld’s *obligative* and *potestative squares* into the two Hohfeldian prisms in [10], discovering the neglected positions of *negative power* and *negative liability*, in an attempt to express the motives of the *prevent-acquire-cure-keep* (PACK) framework [6] in Hohfeld’s terms. In [9], we explored the different pragmatic meanings of agentic negative counterparts of *commitment*, *affordance*, *expectation* and *susceptibility*.

For evaluation of our work on subsumption we considered a sale transaction from different views, modeled in an extension of Petri Nets². The first, simplest representation is that of a simple description of occurrence (Fig. 1). This corresponds in practice to an *event log*. Events are represented with grounded predicates, and the sequence is captured by the structure of the net. Note that the representation does not (globally) reify time. In the second we generalize the model of sale (based on the Dutch civil code) to a general pattern (Fig. 2). In the third we progress to the normative definition of a sale as defined in the Dutch civil code as an agreement between two parties, each promising the other to perform a certain action (Fig. 3). In the fourth, the agent script, institutional positions play the role of reasons weighted before taking a decision, with economic ones, heuristics, etc.

2. Subsumption for positional models expressed as Petri Nets

How to recognize whether, given two models of the types shown above, they are referencing to the same component? In theoretical terms, the transformations of physical or abstract entities preserving (part of) the original structure are called *morphisms*: homomorphism, isomorphism, and intermediate notions between homomorphism and isomorphism, amongst which *bisimilarity* [7]. A complementary approach is log-based analysis, highly tolerant of incomplete knowledge and visibility on the environment, e.g. *re-*

²Logic Programming Petri Nets, see <https://github.com/s113n0/1ppneu>




Figure 1. Example of occurrence: a sale instance.




Figure 2. Example of pattern: a generic sale.




Figure 3. Example of normative specification: a sale transaction.

play fitness [4] quantifies the extent to which the model reproduces logs. Recent works compute fitness in linear time (e.g. [5]), based on a hierarchy of *single-entry-single-exit* (SESE) components. This is particularly relevant for a library of components.

For reasons of space, the *hybrid* approach we propose is presented briefly and informally. Subsumption is checked at different levels. In preparation, we ground both models, i.e. we compute all possible execution paths, obtaining two sets of *stories* specific Σ_S and general Σ_G . Specific stories should be subsumed by at least one general story:

$$\forall story_S \in \Sigma_S, \exists story_G \in \Sigma_G / subsumes(story_G, story_S)$$

Iterating over the steps in the general story, the algorithm looks first to settle a state in the specific story which is subsumed by the current general state. Then it goes further to find a specific event which is subsumed by the general one. If it misses one of the two, it returns false. At this point, to check whether a state subsumes the other, we have to check if each local state (i.e. place/markings coupling) of the general state subsumes a *distinct* local state in the specific state.

```

1: procedure SUBSUMES(general story, specific story)
2:   for general step in general story do
3:     found = false; pos = 0
4:     for specific step after pos in specific story do
5:       gap = 0
6:       if subsumes(general step.state, specific step.state) then
7:         for step after pos + gap in the specific story do
8:           if subsumes(generic step.event, specific step.event) then
9:             pos = current pos in specific story
10:            found = true; break
11:          if found then break
12:          else gap++
13:        if not found then return false
14:      return true

```

3. Discussion and conclusion

Models and results running the subsumption algorithm appear satisfactory so far, and are available to the reader online at <http://justinian.leibnizcenter.org/lnpetri>. The evaluation models have been constructed using Yasper³, as basic Petri nets, and then mapped to our notation. Ongoing efforts are towards strengthening the connection between institutional and intentional positions (*should behave* versus *why*), i.e. the module concerning *pliance*, cf. [10], which is not yet fully integrated at the moment.

References

- [1] A. Boer. *Legal Theory, Sources of Law and the Semantic Web*. IOS Press, Amsterdam, 2009.
- [2] A. Boer and T. Engers. Agile: a problem-based model of regulatory policy making. *Artificial Intelligence and Law*, 21(4):399–423, 2013.
- [3] A. Boer and T. van Engers. An Agent-based Legal Knowledge Acquisition Methodology for Agile Public Administration. *ICAAIL 2011: The Thirteenth International Conference on Artificial Intelligence and Law*, 2011.
- [4] J. C. Buijs, B. F. Van Dongen, and W. M. Van Der Aalst. On the role of fitness, precision, generalization and simplicity in process discovery. *OTM 2012: On the Move to Meaningful Internet Systems*, 7565 LNCS:305–322, 2012.
- [5] J. Munoz-Gama, J. Carmona, and W. M. Van Der Aalst. Single-Entry Single-Exit decomposed conformance checking. *Information Systems*, 46:102–122, 2014.
- [6] D. M. Ogilvie and K. M. Rose. Self-with-other representations and a taxonomy of motives: two approaches to studying persons. *Journal of personality*, 63(3):643–79, Sept. 1995.
- [7] D. Sangiorgi. On the origins of bisimulation and coinduction. *ACM Transactions on Programming Languages and Systems*, 31(4):1–41, 2009.
- [8] P. Schlag. Hiding the Ball. *New York University Law Review*, 71:1681, 1996.
- [9] G. Sileno, A. Boer, and T. V. Engers. Commitments, Expectations, Affordances and Susceptibilities: Towards Positional Agent Programming. In *PRIMA 2015: proc. of the 18th Conf. on Principles and Practice of Multi-Agent Systems*, 2015.
- [10] G. Sileno, A. Boer, and T. van Engers. On the Interactional Meaning of Fundamental Legal Concepts. In *JURIX 2014: proc. of the 27th Conf. on Legal Knowledge and Information Systems*, volume 271 of *Frontiers in Artificial Intelligence and Applications*, pages 39–48. IOS Press, 2014.

³<http://www.yasper.org/>