UNIVERSITY OF AMSTERDAM

UvA-DARE (Digital Academic Repository)

Feature grammar systems. Incremental maintenance of indexes to digital media warehouses

Windhouwer, M.A.

Publication date
2003

Link to publication

Citation for published version (APA):
Windhouwer, M. A. (2003). *Feature grammar systems. Incremental maintenance of indexes to digital media warehouses*. [Thesis, externally prepared, Universiteit van Amsterdam].

General rights
It is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), other than for strictly personal, individual use, unless the work is under an open content license (like Creative Commons).

Disclaimer/Complaints regulations
If you believe that digital publication of certain material infringes any of your rights or (privacy) interests, please let the Library know, stating your reasons. In case of a legitimate complaint, the Library will make the material inaccessible and/or remove it from the website. Please Ask the Library: https://uba.uva.nl/en/contact, or a letter to: Library of the University of Amsterdam, Secretariat, P.O. Box 19185, 1000 GD Amsterdam, The Netherlands. You will be contacted as soon as possible.

UvA-DARE is a service provided by the library of the University of Amsterdam (https://dare.uva.nl)

Download date:18 Nov 2026

Index

abstract attributes, 5
acceptation style, 25
accepting grammar mode, 19
Acoi, 8
Acoi image algebra, 120
Admire, 5
ALGOL 60, 45
alternative production rules, 20, 46
ambiguity, 5, 20, 68
ambiguous feature grammar systems, 39
analysis, 57
AND/OR-graph, 20
annotation extraction algorithm, 5
annotation subsystem, 3
annotations, 4
anonymous symbol, 48
artificial language, 18
atom, 32, 48
atom symbols, 32
atom type, 48
attribute grammars, 97
Australian Open, 128
automaton, 66
auxiliary tree, 82
axiom, 15

back propagation neural network, 57
basic feature grammar system, 29
batch learning algorithms, 58
bidirectional grammars, 19
binary association table (BAT), 99
blackboard architecture, 24
blackbox detector, 56
bottom-up parsing algorithm, 69
bounds, 54
breadth-first parsing algorithm, 70

Chomsky hierarchy, 16
classifier, 57, 95
COBRA, 5, 128
compositional semantics, 5
concept, 6, 54
conceptual level, 126
conditional feature grammar system, 38
conditional grammars, 22
constant, 54
context, 88
context dependency, 6, 113
context globalization, 91
context localization, 91
context-free (CF) grammars, 17
context-sensitive (CS) grammars, 16
controlled named disjunction, 40
controller named disjunction, 40
cooperating distributed (CD) grammar systems, 24
crossed agreements, 17

data repository, 135
database management system (DBMS), 4
dataflow languages, 43
deadlock, 36, 61, 91, 96
deadlock prevention, 36
decision rule, 6, 54, 55
decomposed storage model (DSM), 99
delta operation, 19
dependencies, 33
dependency graph, 111
depth-first parsing algorithm, 69
derivation, 18
derivation mode, 25
derived features, 5
detector, 28, 49
detector confidence, 41, 52

detector symbols, 28
detector version, 62
deterministic, 20, 68
digital media warehouse (DMW), 1
direct derivation, 18
direct self-reference, 91
directional parsing algorithm, 70
disambiguation, 21
document object model (DOM), 86
document type definition (DTD), 101, 103
domain-specific language, 14
dynamically controlled CD grammar system, 26

edge folding, 84
elementary tree, 82
erasing production, 16
exhaustive backtracking parsing algorithm, 75
extended Backus-Naur form (EBNF), 45
extended regular expression languages, 17
extensible markup language, 100
extensible markup language (XML), 50, 86
external change, 7, 62, 114

feature, 6
feature detector engine (FDE), 65
feature detector scheduler (FDS), 111
feature grammar systems, 27
finite automaton (FA), 66
forward axis, 50

general purpose language (GPL), 94
generating grammar mode, 19
generic parser, 82
grammar, 15
grammar component, 24
grammar systems, 24
grammars, 15
grammatical database model, 119
greedy parsing, 47, 85

high-level concept, 6, 54
human interaction, 21

indirect self-reference, 91
instantiation, 32
internal change, 7, 62, 115
internal control, 26
iterative interpretation, 47

key/reference dependency, 114

left path-controlled (lPC) grammar, 34
left path-controlled feature grammar system, 34
left-hand side, 15
left-recursion, 78
leftmost derivation, 18
lexical ambiguity, 21
lexical analysis, 32
lexicon, 32
Linda tuple spaces, 43
linear bounded automaton, 17
linear ordering, 36
list, 53
local ambiguity, 21
logical features, 5
logical level, 126
lookahead, 80
low-level feature, 6
lower bound, 54

machine learning, 6, 57
Magnum, 100
match part, 69
Matlab, 56
memoization, 20, 81, 90
meta-language, 45
Microsoft DirectShow, 43
mild context-sensitivity, 17
mildly context-sensitive feature grammar systems, 41
Mirror, 42
module, 61
Monet, 99
Monet interpreter language (MIL), 99
MOODS, 42
multi-agent systems, 24
multimedia information retrieval, 2
multiple agreements, 17

named disjunctions, 21, 40
namespace, 62

naming conflict, 62
natural language, 13
neural network, 6, 57
non-deterministic, 20, 68
non-directional parsing algorithm, 70
non-terminals, 15

observation, 57
optional, 46
output/input dependency, 6, 114

packed shared forest, 20
parallel communicating (PC) grammar systems, 24
parse forest, 20
parse tree, 19
path operation, 19
path-controlled (PC) grammar, 34
physical level, 126
plugin, 56, 94
polling, 63
positive closure, 46
post-order, 102
post-visitation, 88
pre-order, 102
pre-terminals, 32
pre-visitation, 88
pre/post plane, 102
predicate, 6, 54
predict, 57
prediction part, 69
presentation environment, 136
primitive features, 5
probabilistic parsing, 21
production rules, 15, 46
productions, 15
push-down automaton (PDA), 66
push-down transducer (PDT), 66

quasi-foot, 40, 61
quasi-node, 40, 61
quasi-root, 40, 61
quasi-tree, 40
query clues, 3
query-by-sketch, 2
query-by-text, 2

recursive descent, 86
recursive interpretation, 46, 78
recursively enumerable (RE) grammars, 16
reduce phase, 70
reduced derivation tree (RDT), 93
reduplication, 17
reference, 58, 95
regular (REG) grammars, 17
regular expression language, 17
regular right part grammars (RRPG), 46
regulated rewriting, 21
Relax NG, 103
relevance feedback, 3
revalidation, 117
reverse axis, 50
right-hand side, 15
right-recursive interpretation, 78
Rijksmuseum, 133

Schematron, 103
scope, 62, 88
self-reference, 61, 91
semantic ambiguity, 21
semantic concept, 6, 54
semantic gap, 4
semantic grammar, 32
sentential form, 18
set, 53
shift phase, 70
shredding, 100
similarity, 3
specialized parser, 82
staircase join, 102
star closure, 46
start condition, 26
start symbol, 15, 52, 60, 95
stop condition, 26
stop condition types, 27
structural ambiguity, 21
style repository, 133
subjectivity, 5
substitution language, 32
symbol table, 84
symbols, 15
syntactic ambiguity, 21

terminals, 15

theory, 57
ToolBus, 43
top-down parsing algorithm, 69
transducer, 66
transitive closure, 18
tree adjoining grammars (TAG), 82
tree-controlled grammars, 22
tuple, 53
Type 0 grammars, 16
Type 1 grammars, 16
Type 2 grammars, 17
Type 3 grammars, 17

upper bound, 54

validation, 117
variables, 15

Webspace Method, 127
webspace schema, 127
whitebox detector, 54

XMark, 101
XML document, 50
XML Schema, 103
XPath axis, 50
XPath expression, 50, 93
XPath language, 50
XPath node test, 51
XPath step qualifier, 51, 55
XQuery, 102

yield operation, 19