



UvA-DARE (Digital Academic Repository)

Narrow-line imaging of single strontium atoms in shallow optical tweezers

Urech, A.; Knottnerus, I.H.A.; Spreeuw, R.J.C.; Schreck, F.

DOI

[10.1103/PhysRevResearch.4.023245](https://doi.org/10.1103/PhysRevResearch.4.023245)

Publication date

2022

Document Version

Final published version

Published in

Physical Review Research

License

CC BY

[Link to publication](#)

Citation for published version (APA):

Urech, A., Knottnerus, I. H. A., Spreeuw, R. J. C., & Schreck, F. (2022). Narrow-line imaging of single strontium atoms in shallow optical tweezers. *Physical Review Research*, 4(2), Article 023245. <https://doi.org/10.1103/PhysRevResearch.4.023245>

General rights

It is not permitted to download or to forward/distribute the text or part of it without the consent of the author(s) and/or copyright holder(s), other than for strictly personal, individual use, unless the work is under an open content license (like Creative Commons).

Disclaimer/Complaints regulations

If you believe that digital publication of certain material infringes any of your rights or (privacy) interests, please let the Library know, stating your reasons. In case of a legitimate complaint, the Library will make the material inaccessible and/or remove it from the website. Please Ask the Library: <https://uba.uva.nl/en/contact>, or a letter to: Library of the University of Amsterdam, Secretariat, Singel 425, 1012 WP Amsterdam, The Netherlands. You will be contacted as soon as possible.

Narrow-line imaging of single strontium atoms in shallow optical tweezers

Alexander Urech,^{1,2} Ivo H. A. Knottnerus,^{1,2,3} Robert J. C. Spreeuw^{1,2} and Florian Schreck^{1,2,*}

¹*Van der Waals-Zeeman Institute, Institute of Physics, University of Amsterdam, Science Park 904, 1098XH Amsterdam, The Netherlands*

²*QuSoft, Science Park 123, 1098XG Amsterdam, The Netherlands*

³*Eindhoven University of Technology, P.O. Box 513, 5600MB Eindhoven, The Netherlands*



(Received 11 February 2022; accepted 10 May 2022; published 27 June 2022)

Single strontium atoms held in optical tweezers have so far only been imaged using the broad 1S_0 - 1P_1 transition. For Yb, use of the narrow (183-kHz wide) 1S_0 - 3P_1 transition for simultaneous imaging and cooling has been demonstrated in tweezers with a magic wavelength for the imaging transition. We demonstrate high-fidelity imaging of single Sr atoms using its even narrower (7.4-kHz wide) 1S_0 - 3P_1 transition. The atoms are trapped in nonmagic-wavelength tweezers. We detect the photons scattered during Sisyphus cooling, thus keeping the atoms near the motional ground state of the tweezer throughout imaging. The fidelity of detection is 0.9991(4) with a survival probability of 0.97(2). An atom in a tweezer can be held under imaging conditions for 79(3) seconds allowing for hundreds of images to be taken, limited mainly by background gas collisions. The use of a fully closed (cycling) transition for imaging will provide a useful tool for state specific detection. We detect atoms in an array of 36 tweezers with 813.4-nm light and trap depths of 135(20) μ K. This trap depth is three times shallower than typically used for imaging on the broad 1S_0 - 1P_1 transition. Narrow-line imaging opens the possibility to even further reduce this trap depth, as long as all trap frequencies are kept larger than the imaging transition linewidth. Imaging using a narrow-linewidth transition in a nonmagic-wavelength tweezer also allows for selective imaging of a given tweezer. As a demonstration, we selectively image (hide) a single tweezer from the array. This provides a useful tool for quantum error correction protocols.

DOI: [10.1103/PhysRevResearch.4.023245](https://doi.org/10.1103/PhysRevResearch.4.023245)

I. INTRODUCTION

Optical tweezers have emerged as a powerful tool for quantum applications. They enable state of the art quantum simulation and computation [1–4], high fidelity and long coherence time qubits [5–10], quantum metrology [11–13], quantum chemistry [14,15], among numerous other applications. Optical tweezers with alkaline-earth(-like) atoms, in particular with strontium and ytterbium, have been recently realized, offering new possibilities in expanding these applications [16–18].

In all strontium tweezer experiments demonstrated so far, the fluorescence of single atoms on the broad (30 MHz) 1S_0 - 1P_1 transition at 461 nm was recorded, while simultaneously cooling the atoms on the narrow (7.4 kHz) 1S_0 - 3P_1 transition at 689 nm [4–6,11–13,16,17,19,20]. This “blue imaging” method allows for high-fidelity detection of single atoms in tweezers with high survival probability [16,17,19]. However, blue imaging requires repumpers to close the $5s4d$ 1D_2 decay channel, which can only be done at tweezer wavelengths where also the 1D_2 state is trapped [5,6,11,19]. Furthermore, the slightly

higher scattering rate obtained in the blue imaging process (~ 75 kHz) can only be used as long as the tweezers are sufficiently deep. Any excess heating from the imaging process can then be cooled away after the image. As the trap depth of the tweezer is reduced, the advantage of fast imaging is lost because the scattering rate must also be reduced to balance heating from imaging and cooling. Reducing the tweezer trap depth has the advantages of decreased laser power requirement per tweezer (allowing for more tweezers using a given laser source) and increasing metastable state lifetimes (reduced off-resonant scattering of tweezer light).

A simpler method for imaging alkaline-earth(-like) atoms in tweezers is to use the narrow 1S_0 - 3P_1 transition for both cooling and imaging. Single atom detection by fluorescence imaging on a (less) narrow transition has previously been demonstrated in ytterbium for two different isotopes. In both cases tweezers with a magic-wavelength for the imaging transition were used [7,18].

Here we detect single ^{88}Sr atoms using only the 1S_0 - 3P_1 transition for simultaneous “red imaging” and cooling. We use optical tweezers that are nonmagic for the imaging transition, but magic for the Sr clock transition (1S_0 - 3P_0). We detect the photons scattered during an *attractive* Sisyphus cooling process [19], thus keeping the atoms near the motional ground state of the tweezer throughout imaging.

Attractive Sisyphus cooling is possible at tweezer wavelengths where the excited state experiences a deeper trap depth than the ground state. More specifically, at our tweezer wavelength of 813.4 nm, the excited state ($|e\rangle \equiv ^3P_1(|m_j| = 1)$) confinement is 1.24 times greater than the ground state

*NarrowLineSrTweezerImaging@strontiumBEC.com

Published by the American Physical Society under the terms of the [Creative Commons Attribution 4.0 International](https://creativecommons.org/licenses/by/4.0/) license. Further distribution of this work must maintain attribution to the author(s) and the published article’s title, journal citation, and DOI.




FIG. 1. (a) A sketch of the Sisyphus cooling process at the root of our imaging technique. The tweezer potential is deeper for the excited state (3P_1) than for the ground state (1S_0). The order of events for a cooling cycle is shown from left to right. The atom initially rolls down the ground state potential where it is preferentially excited near the bottom of the potential. The atom then rolls up the steeper excited state potential before decaying back to the ground state at a lower energy. This leads to a reduction in energy per scattered photon related to the trap depth mismatch [19,21]. (b) A simplified schematic of the experimental setup. A high numerical aperture objective ($NA = 0.5$) creates the optical tweezers and collects the atomic fluorescence. A single beam (imaging beam) is used for light assisted collisions, cooling, and imaging in the tweezer array. The polarization of both this imaging beam (\mathbf{E}_{img}) and the SLM tweezer pattern ($\mathbf{E}_{\text{tweezer}}$) are shown. The direction of gravity with respect to the objective is also shown (\mathbf{g}). (c) Averaged fluorescence of strontium atoms in the 6×6 array of tweezers used throughout the majority of this work. We collect photons scattered from the 1S_0 - 3P_1 ($|m_j| = 1$) transition during the cooling process in order to image the atoms in the array. The image is the average of 100 experimental realizations using 500 ms of exposure each. (d) Image obtained by one such experimental run. Approximately half of the tweezer traps are filled on average.

($|g\rangle \equiv ^1S_0$), see Fig. 1(a). This cooling process can be very efficient with a proper choice of parameters, leading to a large reduction in energy per scattered photon, and a small number of scattered photons needed to cool the atom [21]. In addition, the non magic trapping causes the harmonic oscillator states of $|e\rangle$ and $|g\rangle$ to be non orthogonal, for both the radial and axial directions. A single cooling beam can thus remove energy from all directions [19,21].

With balanced heating and cooling from the imaging process, the trap depth can be significantly decreased, reducing the power required per tweezer. Additionally, red imaging can be performed without repumpers, since optical pumping to metastable states is much reduced. The only remaining pumping is due to off-resonant scattering of 813-nm tweezer light when the atom is in $|e\rangle$, which has a low rate that is even

further decreased by using shallow tweezers. Specifically, the calculated off-resonant scattering rate of tweezer photons from an atom in the 3P_1 state is 1.3 Hz under imaging conditions, where the finite fraction of time spent in the excited state is taken into account.

Imaging in shallow tweezers does limit the scattering rate that can be achieved without unacceptable atom loss, for both red and blue imaging. Shallow tweezer imaging therefore requires a longer exposure time for high-fidelity single atom detection compared to imaging in deeper tweezers. We show for red imaging that the maximum scattering rate ($\Gamma/2 \approx 23$ kHz for the 1S_0 - 3P_1 transition, where $\Gamma = 2\pi \times 7.4$ kHz is the transition linewidth) can be closely approached with proper modulation of the frequency and intensity of the cooling beam, while maintaining a lower temperature than when using blue imaging. This allows for a reduction of the trap depth by a factor of ~ 3 , while only marginally increasing the imaging duration and maintaining a near unity detection fidelity and survival probability.

We proceed by presenting an overview of the experimental setup and the procedure for preparing single atoms in Sec. II. In Sec. III, we present our imaging method along with a description of the attractive Sisyphus cooling process, optimized parameters, detection fidelity, and survival probabilities. In Sec. IV we demonstrate the ability to selectively image (dark out) a specific tweezer from the array and we conclude in Sec. V.

II. OVERVIEW OF EXPERIMENTAL SETUP AND PROCEDURE

Similar to previously demonstrated strontium tweezer experiments, we load the optical tweezers with a small and random number of atoms from a magneto-optical trap (MOT) operating on the narrow 1S_0 - 3P_1 transition [4–6,11–13,16,17,19]. Our procedure for creating the MOT is similar to the one of [22], but uses a reduced number of MOT beams to make space for a microscope objective and dynamically moves the MOT from a loading position into the objective focus, see Appendix A.

We create two dimensional arrays of optical tweezers using a phase-only spatial light modulator (SLM) to imprint a phase onto an 813.4-nm laser beam creating an array of foci [1,2]. This array is then imaged onto the narrow linewidth MOT through an $NA = 0.5$ microscope objective. An additional dynamically movable tweezer is created using the same microscope objective and a pair of crossed acousto-optic deflectors (AODs), see Appendix B.

The tweezer trap depth used throughout this paper is $135(20) \mu\text{K}$ unless otherwise specified. For our $1/e^2$ tweezer waist of $\sim 0.84 \mu\text{m}$, the ground-state radial (axial) trap frequencies are $\omega_{\text{radial}} = 43(3)$ kHz [$\omega_{\text{axial}} = 6.6(5)$ kHz], respectively. This trap depth is chosen such that the excited state axial trap frequency [7.3(6) kHz] is comparable to the linewidth of the 1S_0 - 3P_1 transition. We characterize the trap depth and waist of our tweezers spectroscopically on both the $m_j=0$ and $|m_j|=1$ 1S_0 - 3P_1 transitions, see Appendix B. The trap frequencies are calculated from the estimated values of the waist and the measured AC Stark shifts.

Once the tweezers have been loaded and the MOT is switched off, a single (nonretro-reflected) 689-nm beam is used to address the tweezer array during all further experimental stages that need 689-nm light (light-assisted collisions, imaging, cooling, spectroscopy), see Fig. 1(b). This beam, here simply called imaging beam, is linearly polarized perpendicular to the tweezer propagation axis to maximize the fluorescence into the microscope. Additionally, we tune the linear polarization of the tweezer light to match the propagation axis of the imaging beam. This maximises the σ^\pm component of the imaging beam because we operate the tweezers at a 0 G magnetic field making the tweezer polarization the dominant quantization axis.

To prepare tweezers containing either a single or no atom, we use light-assisted collisions to induce pairwise loss, leaving either zero or one atom remaining in each tweezer [23]. The imaging light used in this process is tuned to a frequency between the Stark shifted resonance of the 1S_0 - 3P_1 ($|m_j| = 1$) transition and an electronically excited molecular state that is further red detuned and that asymptotically corresponds to the 3P_1 state [16,24].

We perform imaging by collecting the scattered photons from the Sisyphus cooling process as presented in Sec. III. The fluorescence is collected via the same microscope objective used to generate the tweezers, and then separated using a long pass dichroic mirror with 750-nm cutoff. The collected fluorescence light is sent onto an EMCCD camera [25,26]. The number of photons in 5×5 pixel regions of interest (ROIs) around each tweezer center is summed. We collect photons for 100 ms in order to separate the single atom signal from the background noise of the camera. This procedure leads to a histogram with two peaks, corresponding to zero and one atom in a tweezer, as shown in Fig. 4(a). An atom is assumed to be in a tweezer if the photon number lies above a threshold located between the two peaks, see Sec. III D.

In the previously demonstrated blue imaging technique, the metastable 3P_0 and 3P_2 states must be repumped to the ground state during imaging because of decay of 1P_1 to those metastable states [11,19]. During red imaging, these repumpers are only used to compensate optical pumping into $^3P_{0,2}$ by the tweezer light that can happen when the atom is in the 3P_1 ($|m_j| = 1$) state. However, we find that this is unnecessary for the shallow traps used in this work. Nonetheless, we have the ability to repump the metastable states via the 3S_1 state using two lasers at 679 nm and 707 nm for the 3P_0 and 3P_2 states, respectively.

For all the results presented in this paper, we begin an experimental run by preparing single atoms using the above method followed by an initial image to determine which tweezers are filled. After this, we perform measurements as required by the experiment under consideration. The average initial image of 100 preparations for a 6×6 array and an image of a single run are shown in Figs. 1(c) and 1(d), respectively.

All plots presented are for 100 repetitions of each experiment unless stated otherwise and the data is the average of all 36 tweezer sites. Taking into account the typical tweezer loading efficiency of 50%, each data point consists of approximately 1800 realizations. The error bars for the entire paper show the standard deviation over the array and are dominated by variation originating from tweezer depth inhomogeneities

across the array. The raw data and the analysis tools used in this research can be found in Ref. [27].

III. IMAGING VIA SISYPHUS COOLING

Our imaging and cooling relies on the attractive Sisyphus cooling technique first proposed in [21,28] and more recently observed experimentally in tweezer arrays [5,11,19] as well as in a continuous beam decelerator [29]. We can keep the scattering rate near maximum with near zero trap loss or heating in tweezers as shallow as 135(20) μK by intentionally keeping the imaged atoms slightly hotter than the coldest possible temperature, and by proper choice of imaging/cooling parameters.

A. Sisyphus cooling criteria

Attractive Sisyphus cooling relies on a trap depth mismatch between the excited and ground-state potentials as shown in Fig. 1(a). In addition, three conditions must be fulfilled for the cooling to work. First, the excited state of the atom must experience stronger confinement than the ground state. Second, one must have the ability to excite the atom selectively from the bottom of the potential, and third the excited atom must have sufficient time to move away from the center of the potential before decaying [21]. The first condition is fulfilled in our setup by properly choosing the trapping wavelength, while the second and third conditions can be fulfilled by using the narrow linewidth 1S_0 - 3P_1 transition in strontium.

The first condition is needed for the atoms to lose kinetic energy by rolling up the steeper potential of the excited state before decaying. This allows for a reduction in potential energy on the order of the differential trap depth per scattering event. The narrow linewidth of the transition allows for the atoms to be selectively excited from the bottom of the trap if the differential trap depth is larger than the linewidth. The lifetime of the narrow transition is long enough to satisfy the third condition if the trap frequencies are larger than the linewidth. The atom will then more likely decay near the motional turning point, away from the center of the trap.

B. Optimal cooling

To investigate the performance of our cooling/imaging technique and find optimal cooling parameters, we measure the temperature by the release and recapture method [30]. We switch the tweezers off, wait a time t_{release} before turning them back on again, and then image the atoms to determine their survival fraction. Atoms are lost quicker when they are hotter. The temperature is determined by comparing the survival fraction for several values of t_{release} with Monte Carlo atom trajectory simulations [19,30].

To characterize cooling performance, we start by preparing a sample and detecting which tweezers contain an atom (see Sec. II). We then cool for a time t_{cool} and perform release and recapture. Next, we cool the array again before taking a final image to see which atoms survived and calculate the survival fraction.

The results of such measurements under optimal cooling conditions for three t_{cool} are shown as examples in




FIG. 2. (a) Temperature measurements using the release and recapture method for three different cooling times t_{cool} after taking an image. The red circles show an atom directly after an image ($t_{\text{cool}} = 0$ ms), green squares show a briefly cooled atom ($t_{\text{cool}} = 2$ ms), and blue triangles show an optimally cooled atom ($t_{\text{cool}} = 20$ ms). Error bars show the standard deviation calculated over the 36 atom array. All other errors fall well inside these error bars. The dashed (solid) lines show the results of Monte Carlo simulations for temperatures of $1.8 \mu\text{K}$ ($3 \mu\text{K}$) respectively. As discussed in Sec. III C, we use an interlaced imaging/cooling technique that ends with 1.5 ms of cooling. The time t_{cool} starts after the final 1.5 ms of cooling at the end of the first image, so t_{cool} is the amount of additional cooling. (b) Recapture fraction of a single atom vs the cooling frequency for $t_{\text{cool}} = 20$ ms and $t_{\text{release}} = 60 \mu\text{s}$. Here we vary the cooling frequency both during the period t_{cool} and during the brief cooling phases interlacing the imaging process. The vertical line shown at -663 kHz indicates the approximate Stark shifted resonance of the cooling transition. (c) Average motional quanta \bar{n} , obtained by numerical simulation, in dependence of cooling light detuning at optimum intensity. The cooling transition is indicated as in (b).

Fig. 2(a). The first measurement is taken directly after the first image ($t_{\text{cool}} = 0$ ms, red circles). The second briefly cools the atoms ($t_{\text{cool}} = 2$ ms, green squares). The third approaches the asymptotically coldest achievable temperature by using a long cooling time ($t_{\text{cool}} = 20$ ms, blue triangles).

Comparing this data with release and recapture simulations yields a temperature of approximately $1.8 \mu\text{K}$ (dashed line in same figure) for an optimally cooled atom ($t_{\text{cool}} = 20$ ms), which is consistent with a temperature near the radial motional ground state energy of roughly $T = \frac{\hbar\omega}{2k_b} \sim 1.1 \mu\text{K}$ for our trap depth [30]. The release and recapture simulations are based on classical trajectories and could lead to an overestimation in the temperature as the atom approaches the motional ground state of the trap. Therefore we take this temperature estimate as an upper bound.

To optimize cooling, we vary cooling light frequency or intensity while keeping $t_{\text{release}} = 60 \mu\text{s}$ and $t_{\text{cool}} = 20$ ms fixed. Figure 2(b) shows an example of such a measurement for which the detuning is varied. As explained in Sec. III C, the imaging process is also interlaced with brief cooling phases. Here we vary the cooling frequency both during the period t_{cool} and during the brief cooling stages interlacing

the imaging process. We find the highest recapture fraction, and therefore optimal cooling, for a frequency of -775 kHz from the free space resonance and an intensity of $\sim 88 I_{\text{sat}}$ (Rabi frequency $\sim 2\pi \times 50$ kHz). Note that for frequencies blue of the Stark shifted resonance, atoms are heated out of the tweezer, causing the zero and one atom signals in the histogram to merge. To still distinguish zero and one atom we keep the threshold determined for histograms using optimal detection parameters (our “standard” threshold).

We compare the experimentally determined optimal parameters and the temperature with results of a numerical simulation of the cooling process. The simulation is based on solving the steady state of a Lindblad master equation for a two-level atom in a pair of 1D quantum harmonic oscillators (QHO), one for each internal state $|g\rangle$, $|e\rangle$. The ratio of the QHO frequencies is given by $\omega_g/\omega_e = \sqrt{\alpha_g/\alpha_e} = 0.899$, with $\alpha_{g,e}$ the dynamic polarizabilities at the tweezer wavelength. Choosing a traveling wave for the Sisyphus cooling laser, the transition dipole moments between vibrational states of different QHO’s are calculated as $d_{eg} \langle m | e^{ikx} | n \rangle$, with $|m\rangle$, $|n\rangle$ the vibrational states for internal states $|g\rangle$ and $|e\rangle$, respectively, and d_{eg} the transition dipole moment of the $^1S_0 \rightarrow ^3P_1$ transition.

We find the optimal parameters and the minimum temperature to be in good agreement (10%) with the experimentally found ones. In Fig. 2(c) we show the number of average motional quanta after cooling in dependence of detuning at optimum intensity (all parameters of this simulation are given in Appendix C). At the minimum we obtain $\bar{n} \approx 0.25$, which is in good agreement with measurements using sideband spectroscopy done by another group using the same cooling method [3,6,12].

C. Optimizing the imaging parameters

We now discuss the imaging procedure and optimize its parameters. In a first approach we record the fluorescence of atoms while cooling. We find that the parameters that are optimal for cooling lead to a low scattering rate. The rate increases if the imaging beam frequency is chosen such that the atom is hotter. In the following we determine the imaging frequency and intensity that lead to highest scattering rate. We then explore a method to increase the fraction of atoms that survive imaging: interlaced imaging with brief cooling stages.

The imaging frequency that leads to maximal scattering is found to be near the Stark shifted resonance (trap bottom). The scattering rate increases with imaging beam intensity approaching the theoretical maximum of ~ 23 kHz at our chosen operating intensity $I \sim 350 I_{\text{sat}}$. Deviations of $\pm 50\%$ from this value have barely any effect on the scattering rate where lower intensities than this range cause a detectable decrease in the scattering rate away from the saturated regime. Higher intensities cause unnecessary heating of the atom and excess camera background noise during detection. To clearly distinguish one atom from zero atoms, we image for 90 ms (see Sec. III D).

The scattering rate is maximized for different conditions than the ones leading to optimum cooling. The optimum cooling frequency is not close to the Stark shifted resonance, but approximately 2–3 radial motional sidebands to the red of




FIG. 3. (a) Determination of cooling time scale. After heating the atoms for 90 ms with imaging light only (detuning of -675 kHz and $I \sim 350 I_{\text{sat}}$), we cool them for the time t_{cool} and then measure the survival fraction after release and recapture. We use a fixed release time of $t_{\text{release}} = 60 \mu\text{s}$. (b) Detected atom fraction in a second image versus imaging frequency. The cooling frequency is fixed at -775 kHz from free space resonance of the 1S_0 - 3P_1 transition. Red circles show data recorded using imaging interlaced by 1.5-ms-duration cooling pulses using an optimized duty cycle of 88% imaging and 12% cooling. Grey diamonds show data recorded using imaging without interlaced cooling and instead a 12-ms cooling stage at the end of the image. The detuning is plotted with respect to the free space resonance of the 1S_0 - 3P_1 transition. The vertical-solid line shows the approximate Stark shifted resonance of the transition. The inset displays a vertical zoom onto the three points of best performance. The point at -675 kHz shows the highest survival probability of 0.97(2).

the shifted resonance. This behavior is consistent with the fluorescence being suppressed once the atom is cooled and there are no longer motional quanta to remove, leaving the laser off resonance. The optimum cooling intensity ($\sim 88 I_{\text{sat}}$) is much lower than the intensity used for imaging. Imaging is therefore accompanied by suboptimal cooling, leading to a higher equilibrium temperature than optimum cooling, and potentially to higher atom loss.

We attempt to increase the fraction of atoms that survive imaging by interlacing imaging with cooling pulses. A similar approach of interlaced imaging and cooling was demonstrated for blue imaging in [20]. In order to determine how much cooling is needed we execute a single imaging pulse with the full duration needed for reliable single atom detection (90 ms) followed by cooling. We estimate the temperature change during cooling by measuring the recapture fraction for a release time of $60 \mu\text{s}$, see Fig. 3(a). Cooling proceeds quickly for a few milliseconds, then approaches the steady state for $t_{\text{cool}} \gtrsim 8$ ms. This indicates that about 10% of the total imaging time should be spent on cooling to maintain a low temperature.

To keep the temperature low during the imaging process, we interlace the 90 ms of imaging time with eight cooling pulses of 1.5 ms duration, i.e., we alternate eight times between 11 ms of imaging and 1.5 ms of cooling, each time changing frequency and intensity. This is the standard imaging timing sequence for all images in this work, unless stated otherwise. The duration of one cooling pulse was chosen to allow significant cooling while not wasting time at a low scattering rate for marginal additional cooling, see Fig. 3(a). The cooling pulse time is much longer than the timescales determining a single Sisyphus cooling cycle (axial and radial

trap period, excited state lifetime, and inverse scattering rate) and allows the atom to scatter ≤ 34 photons.

We now reoptimize the imaging frequency to maximize the fraction of detected atoms using imaging interlaced with cooling. This fraction is measured by preparing a sample of single atoms using interlaced imaging with optimized operating parameters (see Sec. II), and then determining how many atoms are also detected on a second interlaced image in dependence of the imaging frequency used for that image, see Fig. 3(b) (red circles). We also show the detected fraction without interlacing imaging with cooling (grey diamonds).

The best performance is reached for a detuning of -675 kHz from the free space resonance (-12 kHz from the Stark shifted resonance), with a detected fraction of 0.97(2). We use this detuning for all images in this paper unless stated otherwise. The benefit of imaging interlaced by cooling is that the survival probability is $\sim 3\%$ higher than what we could obtain without interlaced cooling. This can be clearly seen in the inset of Fig. 3(b) where we zoom in on the points of best performance.

At the points highlighted by the inset, the detected fraction of atoms in the second picture is equivalent to the survival probability. However we specifically choose this alternate label because the reduction in the detected fraction for higher and lower detuning is due to different mechanisms. For blue detuning from the optimum value [right-hand side of the plot in Fig. 3(b)] the reduction is dominated by the probability of an atom to be lost during imaging as evident from an increased variation in collected photon number. The blue detuned light can heat the atom out of the tweezer before sufficient photons can be scattered for detection. In the region red detuned of the optimum value (left-hand side of the plot) the poor detected fraction is instead dominated by insufficient scattering rate as evident from a decreased average number of collected photons. The reduction in scattering rate also leads to the drastically increased error bars at further red detuned frequencies. For frequencies more than 50 kHz away from optimum the zero and one atom signals merge. Again, we use our standard threshold to distinguish zero and one atom.

We compare the temperature after our imaging process (which ends in a 1.5-ms cooling stage) to the one obtained after a long cooling time (20 ms additional cooling) using release and recapture measurements, see Fig. 2(a). Directly after the imaging process the data is well described by a simulation assuming $3 \mu\text{K}$ (red circles and solid line). This is not much above the temperature obtained after long cooling of about $1.8 \mu\text{K}$ (blue triangles and dashed line).

D. Detection fidelity, survival probability and minimum tweezer depth

To distinguish tweezers containing one or zero atoms on fluorescence images we use a photon count detection threshold. We now illustrate this method and determine the optimum detection threshold and the detection fidelity. We measure the fraction of atoms that survive imaging and discuss its dependence on tweezer trap depth. Finally, we compare the lifetime of atoms under cooling and imaging conditions.

Figure 4(a) shows a histogram of the number of collected photons in a tweezer ROI, where the average offset from




FIG. 4. (a) A histogram showing fluorescence photon counts from ROIs around single tweezers during imaging. This histogram combines the results of 1000 experimental runs using a 6×6 tweezer array. The clear separation of the peaks highlights the uniform scattering over the array. The EMCCD counts per ROI have been converted to the number of incident photons. We use a bin size of 0.79 photons (150 EMCCD counts). The dashed line indicates the threshold separating the 0 atom peak (left) from the one atom peak (right). The EMCCD camera has a quantum efficiency of 92% at 689 nm. Fluorescence is collected for 100 ms during which we perform eight cycles consisting of 11 ms of imaging light followed by 1.5 ms of cooling light. (b) The survival fraction vs the time spent under optimized imaging cycles (red circles) and under optimal cooling (blue triangles). The dashed lines show fits to the data (see text).

background photons and camera noise is subtracted. Two distinct peaks are visible: one around zero photons, corresponding to no atom in the tweezer, and another around 50 photons, corresponding to the fluorescence count of a single atom. As is standard procedure [5,11,16,17,19,31,32], we postulate that an atom is present if the photon count is above a detection threshold, marked as dashed vertical line in the histogram. It may happen that randomly very few photons are scattered despite an atom being present in the tweezer or vice versa, leading to a wrong detection result. The detection fidelity is the probability of the detection to be correct. We determine it by calculating the overlap between a skewed Gaussian (fit to the zero atom peak) and a Gaussian (fit to the one atom peak) following the procedure outlined in [32]. As a double check, we calculate the fidelity following the procedure outlined in [20], which does not rely on fitting the histogram. Both methods agree within our quoted uncertainty. Using the detection threshold as an optimization parameter, we obtain a maximum detection fidelity of 0.9991(4) for a $135(20) \mu\text{K}$ trap depth.

The duration of images can be decreased to 50 ms with only a small loss in detection fidelity (fidelity reduced to

0.985). The loss is dominated by misidentifying a filled tweezer as empty at the optimal threshold, and is limited by background light on the camera and not by camera electronic noise. In particular the stray light of the repump lasers contributes to misidentification (the band pass filter in front of the camera insufficiently filters their light). In fact, we obtain a better detection fidelity without using the repump lasers, also because optical pumping to metastable states happens rarely during imaging for our optical tweezer intensities. This is the reason why we do not use the repump lasers during our imaging process for shallow traps.

To determine the probability of an atom to survive the imaging process we record two images in sequence. The probability to detect an atom on the second image if it was present on the first is 0.97(2).

The trap depth can be reduced to $99(15) \mu\text{K}$ without sacrificing detection fidelity. However, once the tweezer trap depth is decreased below the $\sim 135 \mu\text{K}$ level, the chance of recovering the atom on a second image starts to decrease. For example we measure a decrease in survival probability to 0.926(65) for a trap depth of $99(15) \mu\text{K}$.

Survival probability is reduced for trap depths below $\sim 135 \mu\text{K}$ because one of the Sisyphus cooling criteria outlined in Sec. III A is not met. For such low trap depths, the excited state *axial* trap frequency becomes lower than the natural linewidth of the transition ($\sim 7.4 \text{ kHz}$). When the axial trap frequency becomes that small the cooling process does not sufficiently compensate fluorescence recoil heating in the axial direction. This is supported qualitatively by our Sisyphus cooling simulation when we set the trap frequency to the axial value. As the trap frequency is varied to lower values, we see that cooling quickly deteriorates for values below the natural linewidth. This analysis also shows there is still something to be gained in cooling performance from a higher axial trap frequency.

The fact that Sisyphus cooling works for higher trap depths highlights the ability of the single radial cooling beam to remove energy from all directions simultaneously. Imaging at even lower trap depths could be achieved by using closer to spherically symmetric potentials as those in [13] or in a 3D lattice [4], allowing reliable imaging at even lower trap depths. Already the achieved trap depth of $135 \mu\text{K}$ for reliable imaging is three times less than obtained with blue imaging in 813-nm tweezers [19], making it possible for us to obtain three times more tweezers for a given 813-nm laser source power. We note that [17] uses similar trap depths ($200 \mu\text{K}$) to those in our paper albeit at a different tweezer wavelength of 515 nm. At this wavelength and with the higher NA microscope objective used in [17], much higher trap frequencies are obtained. Because of this, we predict that in such a system a similar reduction in trap depth should be possible.

In Fig. 4(b) we show the survival probability over time t_{hold} when continually imaging or when just cooling. For these long measurements we turn on the repump lasers and close the atomic beam shutter. We fit the data by $e^{-(t/\tau)^\alpha}$, where α and τ are fit parameters. For continual imaging cycles the fit provides $\alpha = 1$ and a $1/e$ lifetime of $\tau = 79(3)$ seconds, allowing for hundreds of pictures to be taken of a single atom. This decay of the survival fraction is equivalent to p_1^N , where N is the number of elapsed 100 ms long images and

$p_1 = 0.9986(4)$ [19]. For continuous cooling the fit provides $\alpha = 0.8$ and $\tau = 116(5)$ seconds. The deviation from a pure exponential decay might be due to slowly improving vacuum quality over the course of each measurement, triggered by the atomic beam shutter closure. When analyzing individual tweezers, we find that some tweezers have the same lifetime under cooling and imaging conditions.

The discrepancy between the value of p_1 and our quoted survival probability for a single image is still unknown to us, however we hypothesize a few causes. One cause might be the slowly improving vacuum as mentioned above. Another might be technical issues during the process of recording an image. Such an image recording error would not contribute much to p_1 , as images are only recorded at the beginning and end of N imaging durations. If such hypotheses are true, p_1 would be the more accurate value for the survival probability and achievable for single pictures with technical improvements.

The finite lifetime can have a variety of origins. We verify that the temperature of the atoms stays constant under both investigated conditions, excluding a slow process heating the atoms out of the trap. We find that the lifetime depends on the vacuum quality, as lifetime degrades over months and increases to the values stated above only after flashing titanium sublimation pumps. The decrease in lifetime from cooling to imaging conditions for most tweezer sites indicates that the small trap depth variation between tweezers of 3% make it impossible to optimize cooling and imaging for all tweezers.

We observe day to day changes of the survival probability originating from drifts away from ideal conditions, in particular magnetic field drifts. Magnetic field drifts on the ~ 20 mG level affect the single image survival probability significantly ($\sim 2\%$ reduction).

IV. SITE SELECTIVE IMAGING

Our imaging technique provides an additional advantage. Using an easily achievable differential Stark shift, one can tune a certain tweezer out of resonance with the imaging light used for the rest of the array. This allows for selective imaging of either the remaining tweezers of the array or of the single shifted tweezer. The ability to selectively readout a single atom from the array is a necessary step for error correction in many quantum computation algorithms [33,34].

To demonstrate the ability to select (or dark out) an atom from the image, we use a tweezer created by the crossed AODs to create a deeper potential for a single tweezer site in a 3×3 tweezer array. To characterize site selective images, we record four consecutive images in one experimental run, see Fig. 5. The first image [Fig. 5(a)] is taken directly after single atom preparation, as described in Sec. II. The AODs are then turned on for the second and third image Figs. 5(b) and 5(c), in which we image the single shifted tweezer and the rest of the array respectively. To record atoms in the shifted tweezer, we increase the imaging detuning to -2 MHz (i.e., 1.325 MHz to the red of the usual imaging detuning). In the fourth image we turn off the additional tweezer and again image the entire array [Fig. 5(d)].

We can image the single site such that it is detected in image two with a survival probability of $0.96(2)$, and never appears in image three. Moreover, the entire atom array




FIG. 5. Site selective imaging using an additional tweezer to apply a differential Stark shift to one tweezer. (a) A first image is recorded to check loading. [(b), (c)] After turning on the AOD tweezer on top of the center tweezer, we image first only the center tweezer and then the rest of the array by using respectively appropriate imaging and cooling detunings. (d) When the AODs are turned off, all traps are visible in a final image using the normal imaging detuning. The images show the average fluorescence from 300 experimental realizations.

survives this “dark out” measurement with a probability of $0.95(2)$.

The lower survival probability, in comparison to the value obtained in Sec. III, is due mainly to worse balancing of the trap intensities for the nine trap array used for this measurement. Here the traps were only balanced to about 7% (the value we tend to get from calculated phase patterns before any additional balancing is performed). This variation is larger than the frequency tolerance that we see for our imaging process of about 3.8%, i.e., a 12.5-kHz frequency difference for our Stark shift. Additionally, the cooling frequency and intensity in the deeper single tweezer were not fully optimized. We note that the AC Stark shift chosen here is too small to fully protect quantum information of the remaining atoms but provides an initial proof of concept. However a stronger AC Stark shift, on the order of 20 MHz, could make this feasible.

V. CONCLUSIONS

In conclusion, we have demonstrated the detection of single Sr atoms in shallow tweezers with high fidelity [$0.9991(4)$] and survival probability [$0.97(2)$]. Detection is based on imaging on the red, narrow linewidth 1S_0 - 3P_1 ($|m_j| = 1$) transition. We show that with proper frequency and intensity modulation a high scattering rate can be maintained while keeping the temperature of the atoms low.

Our red imaging technique works for a wide range of trap depths, and for shallow traps, red imaging is advantageous over blue imaging. We need slightly (\sim twofold) increased imaging times (100 ms instead of 50 ms) in comparison to blue imaging on the broad linewidth 1S_0 - 1P_1 transition in deep traps (450 μ K depth) [19]. However, in shallow traps blue imaging is limited by the cooling rate, leading to excessive imaging times in comparison to red imaging [4].

In contrast to blue imaging, red imaging avoids optical pumping of ground state atoms into the metastable states (via 1D_2). Imaging in shallow traps reduces off-resonant scattering of trap light by metastable state atoms ($^3P_{0,2}$), leading to longer coherence times. Red imaging in shallow traps combines both advantages and enables high-fidelity shelving into metastable states for state specific detection or clock readout.

We show that, with a small additional Stark shift, we can isolate a single tweezer of the array from the imaging process. This allows us to selectively image (or hide) a single atom of the array. Through application of a bias field of ~ 50 G, this selective imaging technique could be further extended to *state-selective* imaging for hyperfine ground states in the fermionic isotope. This opens the possibility of imaging more than two hyperfine ground states without disturbing the others. This will be a useful tool for quantum simulations or qudit style quantum computing [35–37].

It should be possible to extend red imaging to situations beyond the specific one examined here. The small potential wells containing the atoms can also be created by optical lattices, or other tightly confining dipole traps, making it possible to use the technique in quantum gas microscopes or 3D lattice clocks. This detection technique should work at nearly all tweezer wavelengths where one of the m_J states of 3P_1 is stronger trapped than the ground state. In particular, using 515-nm tweezers would be an appealing option. This is because red imaging avoids the leakage channel through 1D_2 from which blue imaging suffers [16,17]. Tweezers at this wavelength are also likely to trap most Rydberg states [38–40]. The large polarizabilities at this wavelength, small diffraction limit of the tweezer light, and shallow required trap depth of red imaging would allow for the creation of ≥ 1000 strontium atom tweezer arrays with current laser technology.

ACKNOWLEDGMENTS

We thank the other members of the Strontium Quantum Gasses group at the University of Amsterdam for useful discussions and debugging tips. We also thank the Eindhoven Quantum Computing group led by Servaas Kokkelmans and Edgar Vredenburg for stimulating discussions. This project is supported by the Netherlands Organization for Scientific Research (NWO) under the Gravitation Grant No. 024.003.037, Quantum Software Consortium, and under Grant No. FOM-153. This work is supported by the Dutch Ministry of Economic Affairs and Climate Policy (EZK), as part of the Quantum Delta NL programme.

APPENDIX A: EXPERIMENTAL SEQUENCE

We utilize a unique technique for loading our narrow linewidth MOT in order to create optical access for the micro-




FIG. 6. (a) Detailed sketch of crucial elements of the experimental setup. White arrow from the left indicates the beam of slowed atoms from the oven. The Zeeman slower and repump beams are shown in blue. The horizontal, overlapping blue and red MOT beams are shown in purple. An additional vertically upwards propagating red MOT beam (shown in pale red) provides confinement against gravity. The initial and final red MOT positions are shown as intense red spots. The red MOT is moved vertically 1 cm into the focus of the microscope objective. The 679-nm and 707-nm repump lasers copropagate with the cooling/imaging beam. (b) Schematic of the tweezer setup. The main tweezer array is generated using an SLM. An additional tweezer can be created using a pair of crossed AODs. The SLM and AOD tweezers are combined using a polarizing beam splitter. Both systems are imaged through an $NA = 0.5$ objective onto the atoms. Fluorescence light from the atoms is separated from the tweezer light using a long pass dichroic mirror. The fluorescence is then sent onto an EMCCD camera (Andor Ixon 897). (c) Experimental sequence (numbers in brackets give time spans in ms). The figure uses acronyms for blue MOT (B MOT), broadband red MOT (BBR MOT), single frequency red MOT (SFR MOT) and light assisted collisions (LAC).

scope objective. First, ^{88}Sr atoms from an $\sim 500^\circ\text{C}$ oven are slowed using a Zeeman slower operating on the $2\pi \times 30$ MHz wide 1S_0 - 1P_1 transition at 461 nm. The slowed atoms are then further cooled and compressed by a four beam “blue” MOT, also using the 1S_0 - 1P_1 transition, in a 3D quadrupole field to milli-Kelvin temperatures. This blue MOT consists of two sets of retroreflected beams ($1/e^2$ waist of ~ 12 mm) that are perpendicular to each other and horizontal. Refraining from implementing the usual third MOT beam pair allows us to place the microscope objective along the gravity axis without complications from that beam pair, as shown in Fig. 6(a). This blue MOT is an incomplete trap as it provides no confinement against gravity. However the blue MOT is able to quickly cool and confine the atoms in the horizontal plane, which comprises the only dimension along which atoms entering from the Zeeman slower are fast. A significant fraction of atoms are then trapped in the quadrupole magnetic field (52 G/cm gradient in the axial direction, which is vertical) of the MOT by optical pumping to low-field seeking states of the 3P_2 manifold. This optical pumping is naturally happening when atoms rapidly scatter MOT light and decay from 1P_1 through the $5s4d$ 1D_2 state to 3P_2 .

After quadrupole trap loading, all blue lasers are switched off and the magnetically trapped atoms are repumped back

to the ground state, using a 497-nm laser resonant with the 3P_2 - 3D_2 transition. Simultaneously the quadrupole field gradient is reduced to 0.63 G/cm in the vertical direction. The atoms are then loaded into a five beam narrow linewidth "red" MOT operating on the 1S_0 - 3P_1 transition. Four of the five red MOT beams are overlapped with the blue MOT beams and the fifth beam ($1/e^2$ waist of ~ 6 mm) is propagating vertically upwards.

There is no need for a downwards propagating beam because the upward radiation pressure force is limited by the narrow linewidth and the MOT quadrupole field to a small phase-space region. This force is counter balanced by gravity. The atoms settle into a cloud on the lower part of a shell of equal B-field magnitude below the quadrupole center. This shell is defined by the detuning of the MOT beams being equal to the Zeeman shift induced by the B field. This trap scheme again does not need a beam going through the microscope objective.

The red MOT beams are initially frequency modulated in order to create a comb of frequencies from -60 to -3000 kHz detuning with 20 kHz spacing. The modulation range and intensity of this broadband red MOT are decreased over 181 ms, while a bias field of ~ 0.6 G against gravity is ramped on, raising the atoms by 1 cm, from the center of the vacuum chamber to the focal plane of the microscope objective, by shifting the center of the quadrupole field. An additional small bias field produced by three orthogonal coil pairs is ramped while the MOT position is raised and used to finely position the red MOT onto the tweezer array. The frequency modulation is then switched off and single frequency red MOT beams, with a detuning of -100 kHz and intensity of $8 I_{\text{sat}}$, are used to load the tweezers.

We optimize all parameters of the experiment up to this point on achieving the desired red MOT atom number in a reliable way and in a short time. We find that for MOTs (with our selected detuning) of 5×10^4 to 3×10^6 atoms, the entire tweezer array can be loaded with ≥ 1 atom per site, where on the low end we get slightly below unity filling. On the high end the high density of atoms in the tweezers leads to less than half of the tweezers being filled with atoms, presumably because of additional nonpairwise losses during the light assisted collision step. Because of this robustness to atom number fluctuations, we load the magnetic reservoir for a variable amount of time at the end of an experimental sequence (~ 200 ms). The exact time is determined by the need to store data of the last run on the data analysis computer and the need to prepare the next experimental sequence in the experiment control computer. This procedure creates a MOT of approximately 5×10^5 atoms at a temperature $\leq 1.5 \mu\text{K}$ in the focal plane of our objective.

Slightly before the MOT is switched to single frequency operation, the tweezers are switched on, see also next Appendix. After the red MOT has reached its final position we wait for 50 ms to load the tweezers. Then we switch off the MOT lasers and quadrupole field, and ramp the bias magnetic fields to 0 G at the position of the tweezers.

Single atom detection only worked properly once we spectrally filtered the 689-nm laser light used to induce fluorescence. The source of all 689-nm light is an external cavity diode laser (ECDL) that is short-term stabilized on a reference

cavity with a linewidth of 35 kHz, which in turn is long-term stabilized (in length) on a spectroscopy signal. Light from the ECDL is amplified by injection locked lasers and then used on the experiment. Initially we used light from the ECDL directly to inject the amplifying diodes. This ECDL light is spectrally broadened by servo bumps from the locking electronics and amplified spontaneous emission and we found it impossible to prepare and detect single atoms. We then used the light that is transmitted through and therefore filtered by the reference cavity to inject the amplifying diodes, allowing us to achieve the single atom preparation and detection results presented here. The red MOT behavior did not noticeably change when switching from unfiltered to filtered light.

The light used for light assisted collisions, imaging, and cooling is sent onto the tweezer array via a single beam with a polarization perpendicular to both the tweezer propagation axis and the tweezer polarization, and a $1/e^2$ waist of ~ 1 mm. We find robust single atom preparation of $\sim 50\%$ for a detuning of approximately -100 kHz from the Stark shifted resonance (-750 kHz from free space resonance). We change the intensity of the beam from low ($I \sim 88 I_{\text{sat}}$ for 10 ms) to high ($I \sim 700 I_{\text{sat}}$ for 150–200 ms) then back to low ($I \sim 88 I_{\text{sat}}$ for 10 ms) in order to cool the loaded atoms into the tweezer, induce light assisted collisions [16,23], and cool the single atom before taking the first image of an experimental run.

APPENDIX B: TWEEZER CREATION

The 813.4-nm laser light used for the optical tweezers in our experiment is generated by an external cavity diode laser, which is amplified to 1.7 W using a tapered amplifier (TA). The output of the TA is divided into two optical paths, a main path to create the tweezer array using an SLM (Meadowlark P1920 1920 \times 1152) and a second path for a movable tweezer using AODs (AA opto-electronic DTSXY-400-800), see Fig. 6(b). The main output path is sent through a dispersive prism in order to filter out any amplified spontaneous emission from the TA and is then sent through an acousto-optic modulator for intensity control before being coupled into a fibre. The second path is sent without further filtering into an optical fibre.

The optical tweezers are created by imaging an array of beams through a microscope objective (NA = 0.5, Mitutoyo 378-848-3). An almost arbitrary and stationary pattern of tweezers is created using the SLM. In order to calculate the phase pattern of the desired tweezer pattern we use the weighted Gerchberg-Saxton algorithm [41]. The phase imprinted onto the incident beam by the SLM is a sum of phases including the tweezer array pattern phase, a lens phase to Fourier transform the phase to a real image, a grating phase to separate the zeroth order, and a factory correction phase.

The sum of these phases creates an array of foci ~ 180 cm from the SLM. This array is imaged through the microscope objective (effective focal length $f = 4$ mm) with a field lens of $f = 500$ mm taking care that the array of beams is conjugated onto the aperture of the microscope objective. In this work all results shown have been performed with the SLM creating a square 6×6 array of tweezers unless otherwise noted.

Additional balancing of the tweezer trap depths can be achieved by finetuning the SLM pattern. As a first step we spectroscopically measure the depth of each tweezer by inducing heating on the 1S_0 - 3P_1 ($m_j = 0$) transition, which is weaker trapped than the ground state. The loss feature is then fit with a Gaussian, and the center frequency is extracted for each tweezer. The detuning of this frequency from the free space resonance is proportional to the tweezer intensities. The amplitude of each tweezer, in the pattern to be calculated, is then weighted based on these measured center frequencies. The tweezer phase pattern is then recalculated using these new weights. This procedure allows us to balance the trap depths across the 6×6 array to a standard deviation of approximately 3% [16,30,31]. This procedure was not executed for the 3×3 array used in Sec. IV.

We characterize the depth of our tweezers using spectroscopic method explained above. The error in our trap depth determination has two sources. The choice of either the blue edge frequency or center frequency, based on if a purely thermally broadened line shape or a purely power broadened line shape is fit respectively, provides $15 \mu\text{K}$ of error [16]. An additional $5 \mu\text{K}$ uncertainty comes from the 3% standard deviation of the optimized SLM pattern. For the tweezers used throughout the paper, we estimate a waist of $\sim 0.84 \mu\text{m}$ and an optical power on the atoms of $\sim 2.33 \text{ mW}$ per tweezer. This is in good agreement with our externally measured waist of $\sim 0.78 \mu\text{m}$. The microscope transmission is also characterized externally to be $\sim 36\%$.

The AC Stark shifts depend not only on the light intensity, but also on the polarization of the light and the magnetic field. To zero the magnetic field, we collect fluorescence induced on the 1S_0 - 3P_1 ($m_j = \pm 1$) transitions from many atoms trapped in a tweezer. We assume the frequency with

the maximum fluorescence to be near the bottom of the trap. We then apply B fields along each Cartesian axis separately and look for the zero crossing point where a single fluorescence feature can be seen in the scan of imaging frequency. We measure the tweezer polarization to be linear directly before the microscope objective, and with zero B field see that the measured lines are in good agreement with our polarizability calculations for linearly polarized tweezers ($\alpha(^1S_0) = 286 \text{ a.u.}$, $\alpha(^3P_1 (|m_j| = 1)) = 355 \text{ a.u.}$, and $\alpha(^3P_1 (m_j = 0)) = 199 \text{ a.u.}$). We note that a more robust characterization of the trap depth would also include trap frequency measurements as those in [12,16,17,20], but we have not yet performed such measurements due to either lack of the required laser or technical limitations in our system.

An additional tweezer (or tweezers) can be created using a crossed pair of acousto-optic deflectors (AODs) whose position in the focal plane can be controlled through radio frequency tones sent to the AODs. Unlike the SLM's slow refresh rate, this tweezer can move at speeds sufficient for sorting atoms into defect free arrays, or for quickly applying an additional tweezer for isolating one tweezer from the rest of the array (see Sec. IV).

APPENDIX C: SISYPHUS COOLING SIMULATION PARAMETERS

For the Sisyphus cooling simulation we consider a trap depth of $k_B \times 135 \mu\text{K} = h \times 2.8 \text{ MHz}$. For our estimated waist of $0.84 \mu\text{m}$, this gives a *radial* trap frequency of 43 kHz for the ground state. We calculate the 1S_0 (α_g) and 3P_1 ($|m_j| = 1, \alpha_e$) polarizabilities to be 286 a.u. and 355 a.u. respectively. For the results presented in Fig. 2(c), we use a Rabi frequency of $2\pi \times 42 \text{ kHz}$. We include 15 harmonic oscillator levels in our calculation.

-
- [1] P. Scholl, M. Schuler, H. J. Williams, A. A. Eberharter, D. Barredo, K. N. Schymik, V. Lienhard, L. P. Henry, T. C. Lang, T. Lahaye *et al.*, Quantum simulation of 2D antiferromagnets with hundreds of Rydberg atoms, *Nature (London)* **595**, 233 (2021).
- [2] S. Ebadi, T. T. Wang, H. Levine, A. Keesling, G. Semeghini, A. Omran, D. Bluvstein, R. Samajdar, H. Pichler, W. W. Ho *et al.*, Quantum phases of matter on a 256-atom programmable quantum simulator, *Nature (London)* **595**, 227 (2021).
- [3] J. Choi, A. L. Shaw, I. S. Madjarov, X. Xie, J. P. Covey, J. S. Cotler, D. K. Mark, H.-Y. Huang, A. Kale, H. Pichler *et al.*, Emergent randomness and benchmarking from many-body quantum chaos, [arXiv:2103.03535](https://arxiv.org/abs/2103.03535).
- [4] N. Schine, A. W. Young, W. J. Eckner, M. J. Martin, and A. M. Kaufman, Long-lived Bell states in an array of optical clock qubits, [arXiv:2111.14653](https://arxiv.org/abs/2111.14653).
- [5] K. Barnes, P. Battaglini, B. J. Bloom, K. Cassella, R. Cox, N. Crisosto, J. P. King, S. S. Kondov, K. Kotru, S. C. Larsen *et al.*, Assembly and coherent control of a register of nuclear spin qubits, [arXiv:2108.04790](https://arxiv.org/abs/2108.04790).
- [6] I. S. Madjarov, J. P. Covey, A. L. Shaw, J. Choi, A. Kale, A. Cooper, H. Pichler, V. Schkolnik, J. R. Williams, and M. Endres, High-fidelity entanglement and detection of alkaline-earth Rydberg atoms, *Nat. Phys.* **16**, 857 (2020).
- [7] S. Ma, A. P. Burgers, G. Liu, J. Wilson, B. Zhang, and J. D. Thompson, Universal gate operations on nuclear spin qubits in an optical tweezer array of ^{171}Yb atoms, [arXiv:2112.06799](https://arxiv.org/abs/2112.06799).
- [8] M. J. Martin, Y.-Y. Jau, J. Lee, A. Mitra, I. H. Deutsch, and G. W. Biedermann, A Mølmer-Sørensen gate with Rydberg-dressed atoms, [arXiv:2111.14677](https://arxiv.org/abs/2111.14677) (2021).
- [9] A. Jenkins, J. W. Lis, A. Senoo, W. F. McGrew, and A. M. Kaufman, Ytterbium nuclear-spin qubits in an optical tweezer array, [arXiv:2112.06732](https://arxiv.org/abs/2112.06732).
- [10] S. Ma, A. P. Burgers, G. Liu, J. Wilson, B. Zhang, and J. D. Thompson, Universal gate operations on nuclear spin qubits in an optical tweezer array of ^{171}Yb atoms, [arXiv:2112.06799](https://arxiv.org/abs/2112.06799).
- [11] M. A. Norcia, A. W. Young, W. J. Eckner, E. Oelker, J. Ye, and A. M. Kaufman, Seconds-scale coherence on an optical clock transition in a tweezer array, *Science* **366**, 93 (2019).
- [12] I. S. Madjarov, A. Cooper, A. L. Shaw, J. P. Covey, V. Schkolnik, T. H. Yoon, J. R. Williams, and M. Endres, An Atomic-Array Optical Clock with Single-Atom Readout, *Phys. Rev. X* **9**, 041052 (2019).
- [13] A. W. Young, W. J. Eckner, W. R. Milner, D. Kedar, M. A. Norcia, E. Oelker, N. Schine, J. Ye, and A. M.

- Kaufman, Half-minute-scale atomic coherence and high relative stability in a tweezer clock, *Nature (London)* **588**, 408 (2020).
- [14] W. B. Cairncross, J. T. Zhang, L. R. B. Picard, Y. Yu, K. Wang, and K.-K. Ni, Assembly of a Rovibrational Ground State Molecule in an Optical Tweezer, *Phys. Rev. Lett.* **126**, 123402 (2021).
- [15] S. Burchesky, L. Anderegg, Y. Bao, S. S. Yu, E. Chae, W. Ketterle, K. K. Ni, and J. M. Doyle, Rotational Coherence Times of Polar Molecules in Optical Tweezers, *Phys. Rev. Lett.* **127**, 123202 (2021).
- [16] A. Cooper, J. P. Covey, I. S. Madjarov, S. G. Porsev, M. S. Safronova, and M. Endres, Alkaline-Earth Atoms in Optical Tweezers, *Phys. Rev. X* **8**, 041055 (2018).
- [17] M. A. Norcia, A. W. Young, and A. M. Kaufman, Microscopic Control and Detection of Ultracold Strontium in Optical-Tweezer Arrays, *Phys. Rev. X* **8**, 041054 (2018).
- [18] S. Saskin, J. T. Wilson, B. Grinkemeyer, and J. D. Thompson, Narrow-Line Cooling and Imaging of Ytterbium Atoms in an Optical Tweezer Array, *Phys. Rev. Lett.* **122**, 143002 (2019).
- [19] J. P. Covey, I. S. Madjarov, A. Cooper, and M. Endres, 2000-Times Repeated Imaging of Strontium Atoms in Clock-Magic Tweezer Arrays, *Phys. Rev. Lett.* **122**, 173201 (2019).
- [20] N. C. Jackson, R. K. Hanley, M. Hill, F. Leroux, C. S. Adams, and M. P. A. Jones, Number-resolved imaging of ^{88}Sr atoms in a long working distance optical tweezer, *SciPost Physics* **8**, 038 (2020).
- [21] V. V. Ivanov and S. Gupta, Laser-driven Sisyphus cooling in an optical dipole trap, *Phys. Rev. A* **84**, 063417 (2011).
- [22] S. Stellmer, R. Grimm, and F. Schreck, Production of quantum-degenerate strontium gases, *Phys. Rev. A* **87**, 013611 (2013).
- [23] N. Schlosser, G. Reymond, and P. Grangier, Collisional Blockade in Microscopic Optical Dipole Traps, *Phys. Rev. Lett.* **89**, 023005 (2002).
- [24] T. Zelevinsky, M. M. Boyd, A. D. Ludlow, T. Ido, J. Ye, R. Ciuryło, P. Naidon, and P. S. Julienne, Narrow Line Photoassociation in an Optical Lattice, *Phys. Rev. Lett.* **96**, 203201 (2006).
- [25] M. Hirsch, R. J. Wareham, M. L. Martin-Fernandez, M. P. Hobson, and D. J. Rolfe, A stochastic model for electron multiplication charge-coupled devices—From theory to practice, *PLoS ONE* **8**, e53671 (2013).
- [26] A. Bergschneider, V. M. Klinkhamer, J. H. Becher, R. Klemt, G. Zürn, P. M. Preiss, and S. Jochim, Spin-resolved single-atom imaging of ^6Li in free space, *Phys. Rev. A* **97**, 063613 (2018).
- [27] A. Urech, I. H. A. Knottnerus, R. J. C. Spreeuw, and F. Schreck, Dataset of “Narrow-line imaging of single strontium atoms in shallow optical tweezers”, at <https://doi.org/10.21942/uva.19658910>.
- [28] R. Taïeb, R. Dum, J. I. Cirac, P. Marte, and P. Zoller, Cooling and localization of atoms in laser-induced potential wells, *Phys. Rev. A* **49**, 4876 (1994).
- [29] C.-C. Chen, S. Bennetts, R. González Escudero, F. Schreck, and B. Pasquiou, Sisyphus optical lattice decelerator, *Phys. Rev. A* **100**, 023401 (2019).
- [30] C. Tuchendler, A. M. Lance, A. Browaeys, Y. R. P. Sortais, and P. Grangier, Energy distribution and cooling of a single atom in an optical tweezer, *Phys. Rev. A* **78**, 033425 (2008).
- [31] K. Singh, S. Anand, A. Pocklington, J. T. Kemp, and H. Bernien, A dual-element, two-dimensional atom array with continuous-mode operation, [arXiv:2110.05515](https://arxiv.org/abs/2110.05515).
- [32] I. S. Madjarov, Entangling, controlling, and detecting individual strontium atoms in optical tweezer arrays, Ph.D. thesis, California Institute of Technology, 2021.
- [33] C. Ryan-Anderson, J. G. Bohnet, K. Lee, D. Gresh, A. Hankin, J. P. Gaebler, D. Francois, A. Chernoguzov, D. Lucchetti, N. C. Brown, T. M. Gatterman, S. K. Halit, K. Gilmore, J. Gerber, B. Neyenhuis, D. Hayes, and R. P. Stutz, Realization of Real-Time Fault-Tolerant Quantum Error Correction, *Phys. Rev. X* **11**, 041058 (2021).
- [34] I. Sohn, J. Bang, and J. Heo, Dynamic concatenation of quantum error correction in integrated quantum computing architecture, *Sci. Rep.* **9**, 3302 (2019).
- [35] J. R. Weggemans, A. Urech, A. Rausch, R. Spreeuw, R. Boucherie, F. Schreck, K. Schoutens, J. Minář, and F. Spielman, Solving correlation clustering with QAOA and a Rydberg qudit system: A full-stack approach, *Quantum* **6**, 687 (2021).
- [36] S. Omanakuttan, A. Mitra, M. J. Martin, and I. H. Deutsch, Quantum optimal control of nuclear spin qudecimals in ^{87}Sr , [arXiv:2106.13705](https://arxiv.org/abs/2106.13705).
- [37] D. Banerjee, M. Bögli, M. Dalmonte, E. Rico, P. Stebler, U. J. Wiese, and P. Zoller, Atomic Quantum Simulation of $U(N)$ and $SU(N)$ Non-Abelian Lattice Gauge Theories, *Phys. Rev. Lett.* **110**, 125303 (2013).
- [38] R. Mukherjee, J. Millen, R. Nath, M. P. Jones, and T. Pohl, Many-body physics with alkaline-earth Rydberg lattices, *J. Phys. B: At. Mol. Opt. Phys.* **44**, 184010 (2011).
- [39] T. Topcu and A. Derevianko, Divalent Rydberg atoms in optical lattices: Intensity landscape and magic trapping, *Phys. Rev. A* **89**, 023411 (2014).
- [40] J. T. Wilson, S. Saskin, Y. Meng, S. Ma, R. Dilip, A. P. Burgers, and J. D. Thompson, Trapping Alkaline Earth Rydberg Atoms Optical Tweezer Arrays, *Phys. Rev. Lett.* **128**, 033201 (2022).
- [41] F. Nogrette, H. Labuhn, S. Ravets, D. Barredo, L. Béguin, A. Vernier, T. Lahaye, and A. Browaeys, Single-Atom Trapping in Holographic 2D Arrays of Microtraps with Arbitrary Geometries, *Phys. Rev. X* **4**, 021034 (2014).